

TECHNICAL DATA

TECHNICAL DATA		CRONO F Target 55		CRONO F Target 70	
	Version	4WD		4WD	
ENGINE LAMBORGHINI		1000.3 W EURO II		1000.3 WT EURO II	
Cylinders/Displacement	n°/cm³	3/3000		3/3000	
Aspiration		Natural		Turbo	
Max. homologated power (2000/25/CE)	HP/kW	55/40,5		70/51,5	
Max. homologated power (ECE R24.03)	HP/kW	52/38,5		67/49,5	
Nominal engine speed	rpm	2200		2200	
Max. torque	Nm	205		260	
Max. torque engine speed	rpm	1400-1600		1400-1600	
Torque backup	%	23		22	
Cooling		liquid-oil			
Engine control		mechanical			
Air cleaner		dry with safety cartridge			
Silencer underhood		with vertical exhaust			
		with lateral exhaust			
Fuel tank capacity	litres	50			

DIMENSIONS AND WEIGHTS: with rear tyres		360/70 R 24		380/70 R 24	
Max. length without link arms	mm	3025		3025	
Min. - max. width	mm	1380-1670		1420-1690	
Max. height at safety frame	mm	2080		2100	
Max. height at engine hood	mm	1140		1140	
Max. height at steering wheel	mm	1230		1240	
Ground clearance	mm	270		270	
Wheelbase	mm	1950		1950	
Front track min.- max.	mm	960-1130		960-1130	
Rear track min.- max	mm	730-1020		730-1020	
Minimum steering radius without braking	mm	3520		3540	
Weight with cab	kg	2130		2280	

TRANSMISSION	
Gearbox clutch	mechanically operated
Mechanical gearbox, 5 synchronised gears, 2 gear ranges with underdrive (Min. speed: 1,33 km/h)	20 FWD + 10 REV
Mechanical gearbox, 5 synchronised gears, 2 gear ranges with underdrive and creeper (Min. speed: 0,21 km/h)	30 FWD + 15 REV
Max. speed km/h	40
Shuttle	mechanical, synchronised
Rear differential lock	mechanically operated
Lubrication	forced
BRAKES AND STEERING	
Braking system	all wheel braking, discs in oil bath on all 4 wheels, hydrostatically operated
Parking brake	independent
Trailer braking	hydraulic braking valve
Hydrostatic steering	independent pump
Steering angle	55°

FRONT AXLE	
Drive and differential engagement	mechanically operated
Front differential lock	mechanically operated
REAR P.T.O.	
Clutch	dry, independent operated
Speed	rpm 540-540 ECON-1000
	rpm 540-540 ECON
	rpm 540-540 ECON-synchro
Operation	mechanical, independent
HYDRAULIC LIFT	
Rear power lift	mechanical
Maximum lifting capacity kg	3000
Pump delivery l/min.	45
Auxiliary hydraulic control valves ways	4/6
3 point linkage (link arms and top link)	fixed hitching balls
	automatic hitching
RH link arm and stabilisers	mechanical
DRIVING POSITION	
Gears levers	lateral
Rops	fixed
	folding
Instruments	analog with Check-Panel
Driver's seat	mechanical adjustment with safety belt

30 FWD + 15 REV GEARBOX WITH UNDERDRIVE AND CREEPER - SPEED IN KM/H AT AN ENGINE SPEED OF 2200 RPM WITH 380/70 R 24 REAR TYRES																													
1 L CR	1 L	2 L CR	2 L	3 L CR	3 L	4 L CR	4 L	5 L CR	5 L	1 M CR	1 M	2 M CR	2 M	3 M CR	3 M	4 M CR	4 M	5 M CR	5 M	1 F CR	1 F	2 F CR	2 F	3 F CR	3 F	4 F CR	4 F	5 F CR	5 F
0,21	0,27	0,31	0,36	0,43	0,52	0,60	0,73	0,84	1,02	1,33	1,62	1,91	2,31	2,73	3,32	3,82	4,64	5,32	6,45	7,35	8,93	10,51	12,75	15,06	18,28	21,04	25,54	29,27	35,53
																									40,00*				

The above specifications refer to tractors with all available equipment. For standard equipment and options, refer to the current price list and ask your local dealer for details.

\* = MAX. SPEED EFFECTIVE  
REVERSE SPEED ARE SLIGHTLY LOWER THAN THE CORRESPONDING FORWARD SPEEDS WITHOUT UNDERDRIVE



SPECIALISED LUBRICATION FOR LAMBORGHINI



Headquarters: V.le Cassani, 15 - 24047 Treviglio (BG) Italy  
tel. +39 0363 4211 - [www.lamborghini-tractors.com](http://www.lamborghini-tractors.com)



Certified ISO 9001 by

