

TECHNICAL DATA		GRAND PRIX Target 75	GRAND PRIX Target 95
	Version	4WD	4WD
ENGINE LAMBORGHINI		1000.4 W EURO II	1000.4 WT EURO II
Cylinders/Displacement	n°/cm³	4/4000	4/4000
Aspiration		Natural	Turbo
Max. power (2000/25/CE)	HP/kW	75/55	95/70
Max. power (ECE R24.03)	HP/kW	71/52	90/66
Rated speed	rpm	2300	2500
Max. torque	Nm	257	367
Max. torque engine speed	rpm	1400-1600	1400-1600
Torque rise	%	18	32
Cooling		liquid	d-oil
Engine governor		mecha	anical
Air cleaner		dry with safe	ety cartridge
Underhood silencer		with vertic	al exhaust
Fuel tank capacity	litres	90	110

DIMENSIONS & WEIGHTS: with rear tyres		16.9 R 30	16.9 R 34
Max. length w/o link arms	mm	3700	3780
Width: min max.	mm	1950-2450	1950-2550
Max. height to ROPS	mm	2450	2550
Max. height to hood	mm	2500	2600
Ground clearance	mm	390	450
Wheelbase	mm	2280	2320
Front track: min max.	mm	1440-2130	1430-2140
Rear track: min max	mm	1500-2000	1500-2100
Min. turning radius w/o brakes	mm	4250	4950
Weight with ROPS	kg	3380	3480
Weight with cab	kg	3580	3680

TRANSMISSION									
Main clutch	hydrostatic control								
Mechanical gearbox 5 synchronised gears x 4 ranges (with creeper) (min. speed: 0,40 km/h)	20 FWD + 20 REV								
POWER SPEED gearbox (2 change underdrive) 5 synchronised gears x 4 ranges (with creeper) (min. speed: 0,34 km/h)	40 FWD + 40 REV								
Max. speed km/h	40								
Shuttle	synchronised mechanical								
Rear differential lock	mechanical control electrohydraulic control								
Lubrication	forced								
BRAKES AND STEERING									
Braking	integral, oil-immersed discs on all 4 wheels,								
Draining	hydrostatic control								
Parking brake	independent								
Parking brake	independent								
Parking brake Trailer braking Hydrostatic steering Steering angle	independent hydraulic braking valve								
Parking brake Trailer braking Hydrostatic steering	independent hydraulic braking valve with adjustable steering wheel								
Parking brake Trailer braking Hydrostatic steering Steering angle	independent hydraulic braking valve with adjustable steering wheel 50° mechanical control electrohydraulic control								
Parking brake Trailer braking Hydrostatic steering Steering angle FRONT AXLE	independent hydraulic braking valve with adjustable steering wheel 50° mechanical control								
Parking brake Trailer braking Hydrostatic steering Steering angle FRONT AXLE Front-wheel drive engagement	independent hydraulic braking valve with adjustable steering wheel 50° mechanical control electrohydraulic control mechanical control								

at nevilita lete								
wet mulitplate								
1000								
electrohydraulic with pushbutton								
wet mulitplate								
540-540 ECON-1000-1000 ECON								
Groundspeed P.T.O. with independent output shaft								
electrohydraulic with pushbutton								
mechanical								
3450								
4800 with supplementary jacks (only for Grand Prix 95)								
54								
4/6								
fixed ball ends								
automatic hitching								
mechanical adjustment								
original integrated								
max. lifting capacity: 1500 kg								
original soundproofed, openable windscreen,								
rear screen wiper, air filter, rearview mirrors								
air conditioning, antidust fillter, ventilation,								
heater and forced recirculation								
analogue with Check-Panel								
mechanical adjustment with safety belt								
air suspension with safety belt								

	20 FWD + 20 REV GEARBOX - SPEEDS IN KM/H AT ENGINE SPEED OF 2500 RPM WITH 16.9 R 34 REAR TYRES																		
1 UD	2 UD	3 UD	4 UD	1 L	5 UD	2 L	3 L	4 L	1 M	5 L	2 M	3 M	4 M	1 F	5 M	2 F	3 F	4 F	5 F
0,40	0,59	0,79	1,04	1,12	1,38	1,66	2,21	2,92	3,57	3,87	5,29	7,04	9,29	10,81	12,32	16,02	22,31	28,11	37,31
																			40,00*

					40	FWD	+ 4	O RI	EV P	WO	ER S	PE	D G	EAF	RBO)	(- S	PEE	DS	IN K	M/H	AT	ENG	INE	SPE	ED	OF:	2500	RP	МW	ITH	16.9) R 3	34 R	EAF	TY	RES				
-	1 UD L 1	UD 2	UD L	2 UD	3 UD L	3 UD	4 UD L	1LL	4 UD	1L	5 UD L	5 UD	2LL	2 L	3LL	3 L	4LL	4 L	1ML	5LL	1 M	5 L	2 M L	2 M	3 M L	3 M	4 M L	1FL	4 M	5 M L	1F	5 M	2FL	2 F	3FL	3 F	4FL	4 F	5FL	5 F
	0.34 0	40 (0.51	0.59	0.67	0.79	0.89	0.96	1.04	1.12	1.18	1.38	1.42	1.66	1.89	2.21	2,50	2.92	3.06	3.32	3,57	3,87	4.54	5,29	6.03	7.04	7.96	9.27	9.29	10.56	10.81	12.32	13.73	16.02	18.27	22.31	24.09	28.11	31.98	37.31
	-,-		.,.	-,	-,-	-, -	-,	-,	- /-		, .	,		,	,	,	,	- /-	-,	- ,-	- /-	- /-	,,	-, -	-,,	- /-	,,	-,	-, -	.,	.,,.	,-	-, -	-1-	-7		,,	-,	. ,	40,00*

The above specifications refer to the models with full equipment package. For information on optional and standard equipment, please see current price list or contact your local dealer.

* = EFFECTIVE MAX. SPEED
N.B.: SPEEDS IN REVERSE ARE SLIGHTLY HIGHER THAN THOSE QUOTED FOR THE CORRESPONDING FORWARD GEARS



